## PURCHASE ORDER Department of Education-Schools Division of South Cotabato Supplier: MUSTARD SEED SYSTEMS CORPORATION P.O No. 24-156 October 17, 2024 Date: Address: Door 4, Diana Bldg. Quimpo Blvd., Brgy Bucan, Davao City PR No. DSC-24-08-140 TIN No. 204-332-439-000 (VAT) **Public Bidding** Mode of Procurement: Gentlemen: Please furnish this office the following articles subject to the terms and conditions contained herein: Supply Office, DepEd SDO So. Place of Delivery: Delivery Term: Fifteen (15) Calendar days Date of Delivery: After receipt of the NTP Payment Term: 100% Final Billing Stock/ Property Description Quantity Unit Cost Unit Amount No. Procurement of ICT Equipment for the Upgrading and Maintenance of Existing Network 1 1 1,263,410.00 Infrastructure at SDO South Cotabato 28-Port Gigabit Managed PoE Switch Color: Black Material: powder coated metal No. of port: 28gigabit ports Type of switch: managed switch No. of SFP slot: 4-SFP Ip camera recognition, unique value for cctv network 10 21,342.00 213,420.00 Lifetime management on ruijie cloud at anytime anyware Maximum Upload Speed 500 Mbps and above Maximum download speed 1Gbps and above Number of Ethernet ports: 28 Power consumption: 1-500 Warranty Period: 1 Year Input voltage: 100-240 V AX6000 High-density Outdoor Omni-directional Access Point Wireless Protocol: 802.11ax (WiFi6), 5.95Gbps MIMO:4x4@2.4GHz, 4x4 @5GHz Protection Level: IP68 Dimension: 300mmx300mmx75.5mm (excluding mounting kits) Power Supplu: 802.3bt PoE++, 48V/1A DC 20 20,488.00 409,760.00 Certifications: CE, ROHS Network Port: 1x100/1000/2500 Base-T, 1x1GBase-x SFP Max/Recommended Clients: 512/130 Operating Temperature: 4°C ~65°C Weight: 3.5 kg (excluding mounting kits) 17" Rack LCD Console with Integrated 8 Port Analog KVM Switch Main Input Voltage: 120V -240V Input Connection Type: IEC 60320 C14 Number of rack unit: 1U Cable length: 1.83m Number of cables: 1 Provided equipment: USB KVM cable Single user rack mount kit: PS2 KVM cable NEMA 5-15 power cord Installation guide Firmware upgrade cable Documentation CD Unit C13-C14 power cord 1 210,536.00 210,536.00 Color: black Height: 4.3cm Width: 48.3cm Depth: 71.1cm net weight: 13.77kg Mounting Location:: Front Mounting mode: Rack Mounted Maximum Mounting depth: 104.98cm Minimum mounting depth: 68cm Network frequency: 50/60 Hz Display size: 337.9 (H) x 270.3 (V)/ 17inch Trackball type: LCP display/foldable design

Unit	Uninterruptible power supply 1kVA Output Max Configurable Power (Watts) = 600Watts/1.0kva Output Frequency (Sync to Mains) = 50/60Hz +/- 1 Hz Unsynchronized Topology = Line Interactive Waveform Type= 6 Ms Typical: 10 Ms Maximum Input Transfer Time= 6Ms Typical: 10Ms Maximum Input Input Frequency = 50/60Hz +/-5Hz Auto Sensing Input Voltage Range for Main operations= 170-280v Number of Power cords=1 Batteries & Runtime Battery Type= Lead-Acid Battery Typical Recharge Time=8hrs Nominal Battery Voltage= 12V Expected Battery Life =3-5 Communications & Management Control Panel= Led Status Display with On Line on Battery Audible Alarm=Alarm when on Battery: Distinctive Low Battery Alarm Surge Energy Rating =156joules physical Maximum Height=93mm, 9.5cm Maximum width =161mm, 16.05cm Net weight=5.7kg Color=Black	10	5,732.00	57,320.00
pcs	Vacuum Cleaner 1200 watts power 10liters dust/liquid capacity with blower function Washable ecological HEPA filter With holder support of accessories 2.5meters flexible hos 5.85 meters power 15+1 kPa air pressure Accessories included 3pcs extension tube Brittle brush Crevice Nozzle 2-in-1 brush and round brush Floor/Carpet brush Wet/dry flow brush Wet/dry flow brush Washable HEPA filter Flexible extension tube floor/carpet brush with double sided nylon hair	2	4,300.00	8,600.00
box	Cat 6 Outdoor Cable Outdoor UTP Cable Cat6 (1box/305 Meters)	3	21,531.00	64,593.00
box	UTP Cable Cat Comply with Cat.6 Specifications/-4 pair unshielded twisted pair (UTP) cable	3	9,147.00	27,441.00
pcs	Gigabit Ethernet Switch 24port Standards and Protocols: IEE 802.3i, IEEE 802.3u, IEEE 802.31b, IEEE802.3x Interface: 24 10/100/1000mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDX) Network Media: 10BASE-T: UTO category 3,4,5 cable (maximum 100m) Fan Quality: Fanless Power Supply: 100-240VAC, 50/60Hz Power Consumption Maximum: 13.1W (220v/50Hz) Dimensions: (WxDxH): 11.6*7.1*1.7 in (294*180*44mm) Switching Capacity: 48Gbps Packet Forwarding Rate: 35.7Mbps MAC Address Table: 8K	4	7,035.00	28,140.00

uni	Smart Cache, 1.2GHz Base 4.4 GHz Display: 23.8 inch screen, 1920x108 Memory: 8GB so DIMM DDR4 Up to MHz Storage: 256GB M.2 2280 PCI-E SSE Graphics: Intel UHD Graphics Optical Drive: WITHOUT Integrated 5.0MP Full HD high-sense Webcam: N/A DTS Audio: Built-in stereo speakers WLAN: 802.11ax/ac/a/b/g/n,WiFi 6 Gigabit Ethernet, Front/Side I/O co Card reader: N/A USB 2.0 Type A port/s: 1Rear I/O Co	assor, 10 cores 12 Threads, 10MB Intel Max Frequency 0 resolution 32 GB of Dual-Channel DRR4 3200 0 1 TB 2.5inch 5400 RPM e webcam with 2 stereo microphones 65 and Bluetooth 5 LAN onnectors onnectors	5	48,720.00	243,600.00		
	Brightness (cd/m2): 250nits						
	Aspect ratio:16:9						
	x-x-x-x-Nothin	g follows-x-x-x-x					
		at a material			Php1,263,410.00		
		Sixty-Three Thousand Fo			os		
	illure to make the full delivery within t every day of delay shall be imposed to		one-tentn (1	7 10)			
Conforme:		LEONARD	M. BAI	LALA, CESO	v		
			Schools Division Superintendent				
1d. 441	DIE UNDER MINERIUA	Head of the	Procurin	g entity (HOI	PE)		
	ARD SEED SYSTEMS						
-	CORPORATION						
Signat	ure over Printed Name						
	Date						
Fund Cluster:		ORS/BURS No. :	06-102101-2024-12-08683				
Funds Available	an	Date of the ORS/BURS :	DEC 1 7 2024				
CARL	Accountant III	Amount:		1, 263, 410			
80	(2-23-24						